

E-FIELD PROBE

EF0391

Measuring electric fields from 100 kHz to 3 GHz

using instruments in the NBM-500 family

- ▲ **General public and occupational field exposure from broadcasting, telecoms and industrial equipment**
- ▲ **Isotropic (non-directional) measurement**
- ▲ **64 dB dynamic range without changing measurement range**
- ▲ **Maximum sensitivity starts at 0.2 V/m**

The probe contains three orthogonally arranged dipoles with detector diodes. The three voltages, corresponding to the spatial components, are available individually at the probe output. The NBM basic unit calculates the resulting isotropic field strength.

APPLICATIONS

The probe detects electric fields from 100 kHz to 3 GHz, covering the fields that occur in broadcasting, telecoms, and industry. The high sensitivity of 0.2 V/m and excellent linearity make it ideal for measuring human safety limit values in the general public domain.

PROPERTIES

The probe is designed with mechanical and electrical properties ideal for field use. The probe head is made of foam material to provide effective protection for the sensors, while having excellent RF characteristics. The electric destruction limits for pulsed and continuous wave signals are several times higher than any of the human safety limit values.

CALIBRATION

The probe is calibrated at several frequencies. The correction values are stored in an EPROM in the probe and are automatically taken into account by the NBM instrument. Calibrated accuracy is thus obtained regardless of the combination of probe and instrument.



SPECIFICATIONS ^a

Probe EF0391		Electric (E-)Field	
Frequency range ^(b)	100 kHz to 3 GHz		
Type of frequency response	Flat		
Measurement range	0.2 to 320 V/m (CW) 0.2 to 10 V/m (True RMS)	10 nW/cm ² to 27 mW/cm ² (CW)	10 nW/cm ² to 0.027 mW/cm ² (True RMS)
Dynamic range	64 dB		
CW damage level	800 V/m	170 mW/cm ²	
Peak damage level ^(c)	8 kV/m	17 W/cm ²	
Sensor type	Diode based system		
Directivity	Isotropic (Tri-axial)		
Readout mode / spatial assessment	3 separate axes		
UNCERTAINTY			
Flatness of frequency response ^(d)	±1 dB (1 MHz to 1 GHz)		
Calibration uncertainty not included	±1.25 dB (1 GHz to 2.45 GHz)		
Calibration uncertainty ^(e)	0.8 dB (≤ 300 MHz)		
@ 0.01 mW/cm ² (6.14 V/m)	1.5 dB (> 300 MHz)		
Linearity	±0.5 dB (1.2 to 200 V/m)	±0.5 dB (0.00038 to 10.6 mW/cm ²)	
Referred to 0.01 mW/cm ² (6.14 V/m)	±0.7 dB (200 to 320 V/m)	±0.7 dB (10.6 to 27 mW/cm ²)	
Isotropic response ^(f)	±1 dB		
Temperature response	+0.2/ -1 dB (±0.025 dB/K)		
GENERAL SPECIFICATIONS			
Factory calibration frequencies	0.1/ 0.2/ 0.3/ 1/ 3/ 10/ 27.12 MHz 0.1/ 0.2/ 0.3/ 0.5/ 0.75/ 1/ 1.8/ 2.45/ 2.7/ 3 GHz		
Recommended calibration interval	24 months		
Temperature range	0 °C to +50 °C		
Operating	-40 °C to +70 °C		
Non-operating (transport)			
Humidity	5 to 95 % RH @ ≤25 °C	≤23 g/m ³ absolute humidity	
Size	318 mm x 66 mm Ø		
Weight	90 g		
Compatibility	NBM-500 series meters		
Country of origin	Germany		

(a) Unless otherwise noted specifications apply at reference condition: device in far-field of source, ambient temperature 23±3 °C, relative air humidity 25% to 75%, sinusoidal signal

(b) Cutoff frequency at approx. -3 dB

(c) Pulse length 1µsec, duty cycle 1:100

(d) Frequency response can be compensated for by the use of correction factors stored in the probe memory

(e) Expanded measurement uncertainty. Accuracy of the fields generated to calibrate the probes

(f) Uncertainty due to varying polarization (verified by type approval test for meter with probe). Ellipse ratio included and calibrated for each probe

ORDERING INFORMATION

	Part number
Probe EF0391, E-field for NBM, 100 kHz – 3 GHz, isotropic	2402/01B
Probe EF0391, E-Field, ACC - with accredited (DAkkS) calibration, basic unit required	2402/01B/ACC

Narda Safety Test Solutions GmbH
 Sandwiesenstrasse 7
 72793 Pfullingen, Germany
 Phone: +49 7121 9732 0
 Fax: +49 7121 9732 790
 Email: support.narda-de@L-3com.com
 www.narda-sts.com

Narda Safety Test Solutions
 435 Moreland Road
 Hauppauge, NY 11788, USA
 Phone: +1 631 231-1700
 Fax: +1 631 231-1711
 Email: nardasts@L-3com.com
 www.narda-sts.us

Narda Safety Test Solutions Srl
 Via Leonardo da Vinci, 21/23
 20090 Segrate (Milano), Italy
 Phone: +39 02 2699871
 Fax: +39 02 26998700
 Email: nardait.support@L-3com.com
 www.narda-sts.it

© Names and Logo are registered trademarks of Narda Safety Test Solutions GmbH and L3 Communications Holdings, Inc. - Trade names are trademarks of the owners.