

# Measuring electric fields from 100 kHz to 3 GHz

using instruments in the NBM-500 family

- ▲ **General public and occupational field exposure from broadcasting, telecoms and industrial equipment**
- ▲ **Isotropic (non-directional) measurement**
- ▲ **64 dB dynamic range without changing measurement range**
- ▲ **For high field strengths up to 1300 V/m**

The probe contains three orthogonally arranged dipoles with detector diodes. The three voltages, corresponding to the spatial components, are available individually at the probe output. The NBM basic unit calculates the resulting isotropic field strength.

## APPLICATIONS

The probe detects electric fields from 100 kHz to 3 GHz, covering the fields that occur in broadcasting, telecoms, and industry. The dynamic range from 0.8 V/m up to 1,300 V/m (64 dB) makes the probe ideal for measuring exposure in both the general public and the occupational environment.

## PROPERTIES

The probe is designed with mechanical and electrical properties ideal for field use. The probe head is made of foam material to provide effective protection for the sensors, while having excellent RF characteristics. The electric destruction limit of 2,000 V/m for continuous wave signals is several times higher than any of the human safety limit values.

## CALIBRATION

The probe is calibrated at several frequencies. The correction values are stored in an EPROM in the probe and are automatically taken into account by the NBM instrument. Calibrated accuracy is thus obtained regardless of the combination of probe and instrument.



## SPECIFICATIONS <sup>a</sup>

Probe EF0392		Electric (E-)Field	
Frequency range <sup>(b)</sup>	100 kHz to 3 GHz		
Type of frequency response	Flat		
Measurement range	0.8 to 1300 V/m (CW) 0.8 to 36 V/m (True RMS)	170 nW/cm <sup>2</sup> to 450 mW/cm <sup>2</sup> (CW)	170 nW/cm <sup>2</sup> to 0.35 mW/cm <sup>2</sup> (True RMS)
Dynamic range	64 dB		
CW damage level	2000 V/m	1000 mW/cm <sup>2</sup>	
Peak damage level <sup>(c)</sup>	20 kV/m	100 W/cm <sup>2</sup>	
Sensor type	Diode based system		
Directivity	Isotropic (Tri-axial)		
Readout mode / spatial assessment	3 separate axes		
<b>UNCERTAINTY</b>			
Flatness of frequency response <sup>(d)</sup> Calibration uncertainty not included	±1 dB (1 MHz to 1 GHz) ±1.25 dB (1 GHz to 2.45 GHz)		
Calibration uncertainty <sup>(e)</sup> @ 0.2 mW/cm <sup>2</sup> (27.5 V/m)	0.8 dB (≤ 300 MHz) 1.5 dB (300 MHz to 1.2 GHz) 1.3 dB (≥ 1.2 GHz)		
Linearity Referred to 0.2 mW/cm <sup>2</sup> (27.5 V/m)	+2/-3 dB (1 to 2 V/m) ±1 dB (2 to 4 V/m) ±0.5 dB (4 to 400 V/m) ±1 dB (400 to 1300 V/m)	+2/-3 dB (0.265 to 1.06 μW/cm <sup>2</sup> ) ±1 dB (1.06 to 4.25 μW/cm <sup>2</sup> ) ±0.5 dB (4.25 μW/cm <sup>2</sup> to 42 mW/cm <sup>2</sup> ) ±1 dB (42 to 450 mW/cm <sup>2</sup> )	
Isotropic response <sup>(f)</sup>	±1 dB		
Temperature response	+0.2/ -1 dB (±0.025 dB/K)		
<b>GENERAL SPECIFICATIONS</b>			
Factory calibration frequencies	0.1/ 0.2/ 0.3/ 1/ 3/ 10/ 27.12 MHz 0.1/ 0.2/ 0.3/ 0.5/ 0.75/ 1/ 1.8/ 2.45/ 2.7/ 3 GHz		
Recommended calibration interval	24 months		
Temperature range	0 °C to +50 °C Non-operating (transport) -40 °C to +70 °C		
Humidity	5 to 95 % RH @ ≤25 °C	≤23 g/m <sup>3</sup> absolute humidity	
Size	318 mm x 66 mm Ø		
Weight	90 g		
Compatibility	NBM-500 series meters		
Country of origin	Germany		

(a) Unless otherwise noted specifications apply at reference condition: device in far-field of source, ambient temperature 23±3 °C, relative air humidity 25% to 75%, sinusoidal signal

(b) Cutoff frequency at approx. -3 dB

(c) Pulse length 1μsec, duty cycle 1:100

(d) Frequency response can be compensated for by the use of correction factors stored in the probe memory

(e) Expanded measurement uncertainty. Accuracy of the fields generated to calibrate the probes

(f) Uncertainty due to varying polarization (verified by type approval test for meter with probe). Ellipse ratio included and calibrated for each probe

## ORDERING INFORMATION

	Part number
Probe EF0392, E-Field for NBM, 100 kHz – 3 GHz, High Power, Isotropic	2402/12B
Probe EF0392, E-Field, ACC - with accredited (DAkkS) calibration, basic unit required	2402/12B/ACC

**Narda Safety Test Solutions GmbH**  
 Sandwiesenstrasse 7  
 72793 Pfullingen, Germany  
 Phone: +49 7121 9732 0  
 Fax: +49 7121 9732 790  
 Email: support.narda-de@L-3com.com  
 www.narda-sts.com

**Narda Safety Test Solutions**  
 435 Moreland Road  
 Hauppauge, NY 11788, USA  
 Phone: +1 631 231-1700  
 Fax: +1 631 231-1711  
 Email: nardasts@L-3com.com  
 www.narda-sts.us

**Narda Safety Test Solutions Srl**  
 Via Leonardo da Vinci, 21/23  
 20090 Segrate (Milano), Italy  
 Phone: +39 02 2699871  
 Fax: +39 02 26998700  
 Email: nardait.support@L-3com.com  
 www.narda-sts.it

© Names and Logo are registered trademarks of Narda Safety Test Solutions GmbH and L3 Communications Holdings, Inc. - Trade names are trademarks of the owners.