

E-FIELD PROBE

EF5091

Measuring electric fields from 300 MHz to 50 GHz

using instruments in the NBM-500 family

- ▲ **Field exposure from satellite communications and radar in the occupational environment, leak detection**
- ▲ **Isotropic (non-directional) measurement**
- ▲ **True RMS indication even with multiple, superimposed, strong pulsed signals**

The probe contains three orthogonally-arranged thermocouple sensors. Each sensor consists of several thermocouples, which together form a dipole. The output voltage from the thermocouple is proportional to the coupled power level, regardless of the signal shape. The isotropic measurement value is obtained by addition within the probe.

APPLICATIONS

The probe detects electric fields from 300 MHz to 50 GHz, covering the fields found in satellite communications and radar equipment. The use of thermocouples naturally results in a true RMS reading, making the probe particularly suitable for measuring human safety limit values in a multi-frequency environment.

PROPERTIES

The probe is mechanically and electrically robust. The probe head is made of foam material to provide effective protection for the sensors, while having excellent RF characteristics. The sensors can handle high impulse power levels.

CALIBRATION

The probe is calibrated at several frequencies. The correction values are stored in an EPROM in the probe and are automatically taken into account by the NBM instrument. Calibrated accuracy is thus obtained regardless of the combination of probe and instrument.



SPECIFICATIONS ^a

Probe EF5091	Electric (E-)Field	
Frequency range ^(b)	300 MHz to 50 GHz	
Type of frequency response	Flat	
Measurement range	8 to 614 V/m	17 μ W/cm ² to 100 mW/cm ²
Dynamic range	37 dB	
CW damage level	1500 V/m	0.6 W/cm ²
Peak damage level ^(c)	27 kV/m	200 W/cm ²
Sensor type	Thermocouple (inherent True RMS detection)	
Directivity	Isotropic (Tri-axial)	
Readout mode / spatial assessment	Combined 3-axis (RSS)	
UNCERTAINTY		
Flatness of frequency response ^(d) Calibration uncertainty not included	± 1.25 dB (1.8 GHz to 40 GHz)	
Calibration uncertainty ^(e) @ 1 mW/cm ² (61.4 V/m)	± 1.5 dB (300 MHz to 1.2 GHz) ± 1.3 dB (≥ 1.2 GHz to 45.5 GHz)	
Linearity Referred to 1 mW/cm ² (61.4 V/m)	± 1 dB (24 to 61.4 V/m) ± 0.3 dB (> 61.4 V/m)	± 1 dB (0.15 to 1 mW/cm ²) ± 0.3 dB (> 1 mW/cm ²)
Isotropic response ^(f)	± 1 dB	
Temperature response ^(g)	± 0 dB	
GENERAL SPECIFICATIONS		
Calibration frequencies	0.3/ 0.75/ 1.8/ 2.45/ 4/ 5/ 6/ 8.2/ 9.3/ 10/ 11/ 18/ 26.5/ 40/ 45.5 GHz	
Recommended calibration interval	24 months	
Temperature range		
Operating	0 °C to +50 °C	
Non-operating (transport)	-40 °C to +70 °C	
Humidity	5 to 95 % RH @ ≤ 25 °C	≤ 23 g/m ³ absolute humidity
Size	318 mm x 66 mm \varnothing	
Weight	90 g	
Compatibility	NBM-500 series meters	
Country of origin	USA	

(a) Unless otherwise noted specifications apply at reference condition: device in far-field of source, ambient temperature 23 ± 3 °C, relative air humidity 40% to 60%, sinusoidal signal

(b) Cutoff frequency at approx. -3 dB

(c) Within any interval of 10ms an average value of 0.6 W/cm² and a peak value of 200 W/cm² should not be exceeded

(d) Frequency response can be compensated for by the use of correction factors stored in the probe memory

(e) Accuracy of the fields generated to calibrate the probes

(f) Uncertainty due to varying polarization (verified by type approval test for meter with probe). Ellipse ratio included and calibrated for each probe

(g) The conversion factor of thermocouple sensors is inherently not dependent on environmental temperature

ORDERING INFORMATION

	Part number
Probe EF5091, E-field for NBM, thermocouple, 300 MHz – 50 GHz, isotropic	2402/03B
Probe EF5091, E-field, ACC - with accredited (DAkkS) calibration, basic unit required	2402/03B/ACC

Narda Safety Test Solutions GmbH
 Sandwiesenstraße 7
 72793 Pfullingen, Germany
 Tel. +49 7121 97 32 0
 Fax +49 7121 97 32 790
 support.narda-de@L-3com.com
 www.narda-sts.com

Narda Safety Test Solutions
 435 Moreland Road
 Hauppauge, NY 11788, USA
 Phone +1 631 231-1700
 Fax +1 631 231-1711
 NardaSTS@L-3COM.com
 www.narda-sts.us

Narda Safety Test Solutions Srl
 Via Leonardo da Vinci, 21/23
 20090 Segrate (Milano), Italy
 Phone +39 02 26 998 71
 Fax +39 02 26 998 700
 nardait.support@L-3com.com
 www.narda-sts.it

© Names and Logo are registered trademarks of Narda Safety Test Solutions GmbH and L3 Communications Holdings, Inc. - Trade names are trademarks of the owners.